

STIRRERS

The *DINKO* stirrer is provided of very silent sealed motors requiring minimal maintenance, permanently lubricated, with protection to overloads

The electronic speed control is progressive and precise with high torque even at a low speed

Unit is encased in all plastic housing of reduced size and closed for the protection against gases and liquids. An integral 225x12 mm Ø rod is fitted so that stirrer can be easily mounted to a support stand, not included. The stirrer shaft is interchangeable.

The speed control is by 7 speed selectors with reverse speed in the model D-13 and D-14, while in the D-15 and D-15BR models is by an external continuous regulation module with retractile cable. Supplied without stirrer shaft, or support stand.

STIRRER Model D-15 and D-15BR

For liquids of medium viscosity / Maximum volume of mixing: 15 liters

Adjustable speed: 100 to 3400rpm..

Stirrer weight: 1 Kg. Control module weight: 300g / Stirrer size, without rod: 175 high x 60mm Ø

Rod size: 225 long x 12mm Ø. Control module size: 150 x 150 x 70mm

Operation: 240V 50/60Hz. 100W. **Code 1.8002.00**

STIRRERS Model D-15BR, low speed of continuous control like D-15

For liquids of medium viscosity / Maximum volume of mixing: 15 liters. Without stirring bar

0-5rpm. **Code 1.8002.15**

0-10rpm. **Code 1.8002.14**

0-80rpm. **Code 1.8002.13**

0-150rpm. **Code 1.8002.12**

0-300rpm. **Code 1.8002.10**



D-15 and D-15BR

STIRRER Model D-14

For liquids of medium viscosity

Maximum volume of mixing: 15 liters

Selector of 7 speeds maximum 3400rpm.

Stirrer weight: 1Kg / Stirrer size without rod: 175 high x 60mm Ø.

Rod size: 225 long x 12mm Ø

Operation: 240V 50/60Hz. 100W. **Code 1.8001.00**

STIRRER Model D-13

Selector of 7 speeds, maximum 4400rpm / Maximum volume of mixing: 2 liters

Stirrer weight: 0,8Kg / Stirrer size without rod: 175 high x 60mm Ø

Rod size 225 long x 12mm Ø / Operation: 240 V 50/60Hz. 75W. **Code 1.8000.00**

Code 1.8000.15 with continuous speed control like D-15

D-14 and D-13

Code	Articles
1.8002.00	Stirrer D-15, 100 to 3400 rpm, without stirring bar
1.8002.15	Stirrer D-15BR, 0 to 5 rpm., without stirring bar
1.8002.14	Stirrer D-15BR, 0 to 10 rpm., without stirring bar
1.8002.13	Stirrer D-15BR, 0 to 80 rpm., without stirring bar
1.8002.12	Stirrer D-15BR, 0 to 150 rpm., without stirring bar
1.8002.10	Stirrer D-15BR, 0-300 rpm., without stirring bar
1.8001.00	Stirrer D-14, 7 speeds, max. 3400rpm, without stirring bar
1.8002.05	Stirring shaft stainless steel fixed paddle 300mm long x 8mm Ø, 60mm tour for D-14, D-15 and D-15BR
1.8002.04	Stirring blade stainless steel 300mm long x 8mm Ø, 70mm Ø tour for D-14, D-15 and D-15BR
1.8000.00	Stirrer D-13, 7 speeds, max. 4400rpm, without stirring bar
1.8000.15	Stirrer D-13C, continuous speed control, max. 4400rpm, without stirring bar
1.8000.01	Stirring shaft blade stainless steel 200mm x 6mm Ø, 50mm Ø tour for D-13
1.8000.07	Stirring shaft paddle stainless steel 200mm long x 6mm Ø, 40mm Ø tour for D-13
SUPPORT STANDS	
1.8003.00	Stand type A, 260 x 260mm, without rod or double clamp
1.8003.01	Support rod stainless steel 600 mm long x 12mm Ø
1.8000.09	Clamp, double for D-13, D-14 and D-15
1.8003.06	Stand complete, base 300 x 150mm, support rod 700mm long and double clamp (1.8009.09)



Stand complete 1.8003.06



Double clamp 1.8009.09



Shaft stirring

Distributor:

www.dinko.es

CE